



## Telescopic lance TL 14 C

Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.




### 1 Multifunctional use

- For window, facade and solar panel cleaning with osmosis water.
- For high-pressure cleaning or low-pressure cleaning with wash brushes.



### 2 Maximum ergonomics

- Anti-spin lock of the lances for safe and ergonomic working.
- Quick-release fasteners for fast and simple loosening of the lance clamping.



### 3 Very user-friendly

- Tool-free adjustment of the clamping force at the quick-release fasteners.
- With clamping hooks to guide water hose outside the lance.



### 4 Maximum safety

- Haptic and visual pull-out stopper avoids unintentional disassembly.
- Non-electroconductive base-lance element.



## Telescopic lance TL 14 C

### Technical data

<b>Order no.</b>		4.762-613.0
<b>EAN code</b>		4054278716442
<b>Length of the telescopic handle</b>	m	2.4-14
<b>Inlet temperature</b>	°C	max. 60
<b>Material</b>		Carbon
<b>Elements</b>		10
<b>Connection thread</b>		M 18
<b>Weight incl. packaging</b>	kg	10.15

### Equipment

<b>Vacuuming</b>	■
<b>Tool less clamp force adjustment</b>	■
<b>Anti-Spin</b>	■
<b>Tool-less clamp force adjustment</b>	■
<b>Hose hook</b>	■
<b>Pull out stopper</b>	■

# TELESCOPIC LANCE TL 14 C

## 4.762-613.0



		Order no.	Flow rate	Inlet temperature	Length	Length	Price	Description	
<b>Teleskopstangen</b>									
TL low pressure adapter	1	4.580-097.0		max. 40 °C				TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	<input type="checkbox"/>
TL high pressure adapter	2	4.775-154.0		max. 60 °C				TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	<input type="checkbox"/>
TL vacuum cleaner adapter	3	9.751-306.0						TL suction cup for 10 and 14 m long telescopic lances comprising suction bend connection (DN 35, DN 40) and connection for the suction nozzles.	<input type="checkbox"/>

Available accessories.

# TELESCOPIC LANCE TL 14 C

## 4.762-613.0



		Order no.	Flow rate	Inlet temperature	Length	Length	Price	Description	
<b>Schläuche</b>									
iSolar HP hose 14	1	6.392-976.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	<input type="checkbox"/>
Water hose 25 m	2	6.392-578.0		max. 60 °C				Water hose (25 m) for water connection to brushes mounted on telescopic lances for window, façade and solar power installation cleaning.	<input type="checkbox"/>
Water hose 50 m	3	6.392-579.0		max. 60 °C				50-metre transparent water hose as supply line for the brushes mounted on telescopic lances for window, façade and solar power installation cleaning.	<input type="checkbox"/>

Available accessories.

# TELESCOPIC LANCE TL 14 C

## 4.762-613.0



		Order no.					Price	Description	
<b>Machine accessories</b>									
Shoulder strap universal	1	2.042-016.0						Ergonomic and convenient universal shoulder strap. For long, fatigue-free work with leaf blowers, lawn trimmers or multi-tools from Kärcher.	<input type="checkbox"/>

Available accessories.